

Compatibility

- VISCA Protocol
- PELCO-D Protocol
- PELCO-P Protocol

What's in the Box?

- Three-axis control keyboard
- RS232 cable
- DC12V Power Supply
- Manual



Features

- Durable Metal Housing
- VISCA, PELCO- P & D
- On Screen Display
- Variable Speed Controls
- Real Time Status Display
- Short Circuit Protection
- Pan, Tilt, Zoom Control
- Iris, Focus, Presets & More

HuddleCamHD

Model No: HC-JOY

Easy pan, tilt & zoom controls for any RS-232 VISCA protocol camera! Controls pan & tilt with variable speed. Use 2 & 3 dimensional joystick with "twist" control of focus and zoom



LCD Display

1. Menu options displayed here

Main Keys

2. Setting and calling presets and changing parameters

Camera Control Buttons

3. Includes: Open, Close, Far, Near, Tele and Wide

4. Joystick

Three-Axis Joystick Controller

5. Function Keys

Programmable function keys

6. DB9 Connection

For RS-232 Camera Control

7. RS422/485 Connection

Used for RS422/485 camera control

8. RJ45 Connection

Used for RS485 camera control

9. Power Connection

12V Power Connection

Specifications

Key Technical Specifications

Connections:	RS-232, RS-485, RS-422
Baud Rate:	1200/2400/4800/9600 bps
Interfaces:	RJ45: RS485; 6SCT: RS485/RS422; DB9: RS232.
Maximum Cameras:	Control up to 256 Cameras
Maximum Distance:	3,937' (1200m) using 24 guage twisted pair

Operational Specifications

Power:	5W (12VDC)
Working Temp:	14° F to 122° F (-10° to +50° C).
Working Humidity:	10 ~ 90% (non-condensation)
Weight:	2.32 lbs 1.05 kg
Dimensions:	10.69"(L) x 7.5"(W) x 4.06(H) 271.5mm(L) x 190.5mm(W) x 103.2mm(H)















HuddleCamHD




Reliable USB Conference Cameras

From 3X - 30X, We've got you covered








Product Line

	HC3X-BK-G2		HC3X-WH-G2	3X optical zoom, 36-81° HFOV, USB 2.0 video up to 1080P-30
	HC10X-720-BK		HC10X-720-WH	10X optical zoom, 7-57° HFOV, USB 2.0 video up to 720P-30
	HC3XW-GY-G2		HC3XW-WH-G2	3X optical zoom, 33-92° HFOV, USB 3.0 video up to 1080P-30
	HC10X-GY-G3		HC10X-WH-G3	10X optical zoom, 8-61° HFOV, USB 3.0 video up to 1080P-30
	HC20X-GY-G2		HC20X-WH-G2	20X optical zoom, 5-58° HFOV, USB 3.0 video up to 1080P-30
	HC30X-GY-G2		HC30X-WH-G2	30X optical zoom, 4-63° HFOV, USB 3.0 video up to 1080P-30




Control Accessories

	HC-JOY	RS232, RS485, RS422, 3D Joystick and Keyboard, VISCA, Pelco-P, Pelco-D
	DB9M-F-xx	Extension Cable, DB9M-F, Plenum, 4 lengths shown in ft. (xx=25, 50, 75, 100)
	VISCA-xx	Daisy Chain Cable, miniDIN8-MM, Plenum, 4 lgs in ft. (xx=25, 50, 75, 100)

Mounting Accessories

	HCM-1-BK		HCM-1-WH	Small Wall Mount, mounts directly to wall or box with supplied hardware
	HCM-2-BK		HCM-2-WH	Large Wall Mount, mounts directly to wall or box with supplied hardware
	HCM-1C-WH			Small Open Ceiling Mount, mounts to 1"NPT pipe
	HCM-2C-WH			Large Open Base Ceiling Mount, mounts to 1"NPT pipe
	PT-CM-1-BK			Surface Ceiling Mount, mounts directly to ceil or box w/ supplied hardware

Conference Audio

	HP-AIR-BK		HP-AIR-WH	Wireless Speakerphone with USB receiver
	HP-AIR-BA-BK			Wireless Speakerphone with USB receiver and external amplifier feed

